

QUY150 | 履带起重机

起重性能参数表 Total rated lifting load

主起重臂额定起重量		Rated boom lifting capacity										
幅度(m)	臂长(m)	52	55	58	61	64	67	70	73	76	79	82
12		48.0	47.6	42.2								
14		40.0	39.0	38.8	38.6	38.0	35.0	32.0				
16		33.8	33.6	33.4	33.2	33.0	30.0	28.0	26.9	25.0	21.5	20.1
18		30.0	29.8	29.6	29.2	28.8	28.0	27.2	26.2	24.2	21.4	19.5
20		26.0	25.7	25.5	25.3	25.0	24.8	24.3	23.7	23.2	20.6	18.8
22		23.4	23.2	23.0	22.0	21.8	21.5	21.3	20.9	20.4	19.9	18.1
24		20.6	20.4	20.0	19.5	19.3	19.1	19.0	18.5	18.1	17.6	16.8
26		18.0	17.7	17.6	17.4	17.1	16.9	16.8	16.6	16.2	15.7	15.2
28		16.6	16.4	16.2	16.0	15.8	15.5	15.0	15.0	14.6	14.1	13.7
30		15.7	15.5	15.3	15.0	14.0	13.6	13.4	13.2	13.2	12.8	12.4
32		14.0	13.6	13.3	13.0	12.6	12.2	12.0	12.0	12.0	11.7	11.2
34		13.2	13.0	12.6	12.0	11.6	11.1	11.0	11.0	11.0	10.7	10.3
36		11.5	11.2	11.0	10.8	10.5	10.2	10.0	10.0	10.0	9.8	9.4
38		10.4	10.1	9.9	9.6	9.4	9.2	9.1	9.0	9.0	9.0	8.6
40		9.8	9.6	9.4	8.9	8.7	8.6	8.5	8.5	8.4	8.3	8.0
42		9.4	8.8	8.6	8.2	8.0	7.9	7.7	7.7	7.7	7.6	7.4
44		8.8	8.0	7.7	7.4	7.3	7.3	7.1	7.1	7.1	6.9	6.8
46			7.4	7.2	7.0	6.9	6.9	6.7	6.6	6.5	6.2	6.1
48			7.0	6.8	6.6	6.4	6.4	6.4	6.2	6.0	5.8	5.4
50				6.5	6.2	6.0	5.9	5.9	5.6	5.3	5.0	4.9
52					6.0	5.5	5.4	5.3	5.0	4.7	4.5	4.3
54					5.7	5.3	5.0	4.8	4.6	4.3	4.0	3.8
56						5.0	4.5	4.4	4.1	3.8	3.5	3.4
58							4.1	4.0	3.8	3.4	3.1	2.9
60								3.6	3.2	3.0	2.7	2.5
62								3.3	3.0	2.6	2.4	2.2

注: 1.表中所示起重量的单位为t。

2.表中所示起重量包括吊具和附件的重量。

Note: 1.The unit of lifting capacity is ton.

2. Lifting capacity in the table includes the weight of sling and accessories.

CRAWLER CRANE

起重性能参数表 Total rated lifting load

副起重臂额定起重量 Rated jib lifting capacity

幅度 Radius (m)	主 臂 Boom 46m							
	副臂安装角10° Jib erection angle 10°				副臂安装角30° Jib erection angle 30°			
	副臂 Jib 12m	副臂 Jib 18m	副臂 Jib 24m	副臂 Jib 30m	副臂 Jib 12m	副臂 Jib 18m	副臂 Jib 24m	副臂 Jib 30m
14.0	15.0							
16.0	15.0							
18.0	15.0	12.0			13.0			
20.0	15.0	12.0	8.0		13.0			
22.0	15.0	12.0	8.0	4.0	13.0	8.0		
24.0	15.0	12.0	8.0	4.0	13.0	8.0		
26.0	15.0	12.0	7.8	4.0	13.0	8.0	6.0	
28.0	15.0	12.0	7.6	4.0	12.6	8.0	6.0	
30.0	15.0	12.0	7.4	4.0	12.2	8.0	6.0	3.0
32.0	14.8	11.5	7.3	4.0	11.8	8.0	6.0	3.0
34.0	13.0	10.9	7.1	4.0	11.5	8.0	6.0	3.0
36.0	12.0	10.5	6.9	3.9	11.2	7.8	5.8	3.0
38.0	11.0	10.3	6.7	3.8	10.8	7.6	5.7	3.0
40.0	10.4	10.0	6.5	3.7	10.2	7.4	5.5	3.0

QUY150 | 履带起重机

起重性能参数表 Total rated lifting load

副起重臂额定起重量 Rated jib lifting capacity

幅度 Radius (m)	主 臂 Boom 70m							
	副臂安装角10° Jib erection angle 10°				副臂安装角30° Jib erection angle 30°			
	副臂 Jib 12m	副臂 Jib 18m	副臂 Jib 24m	副臂 Jib 30m	副臂 Jib 12m	副臂 Jib 18m	副臂 Jib 24m	副臂 Jib 30m
18.0	15.0							
20.0	15.0	12.0						
22.0	15.0	12.0			13.0			
24.0	15.0	12.0	8.0		13.0			
26.0	15.0	12.0	8.0	4.0	13.0	8.0		
28.0	15.0	12.0	8.0	4.0	13.0	8.0		
30.0	14.3	12.0	8.0	4.0	13.0	8.0	6.0	
32.0	12.9	12.0	8.0	4.0	13.0	8.0	6.0	
34.0	11.7	11.7	7.8	4.0	11.7	8.0	6.0	3.0
36.0	10.7	10.7	7.6	4.0	10.7	8.0	6.0	3.0
38.0	9.8	9.8	7.5	4.0	9.8	8.0	6.0	3.0
40.0	9.0	9.0	7.4	4.0	9.0	8.0	6.0	3.0
42.0	8.2	8.2	7.2	4.0	8.2	8.0	6.0	3.0
44.0	7.5	7.5	7.1	4.0	7.5	7.5	5.8	3.0
46.0	7.0	7.0	7.0	3.9	7.0	7.0	5.6	3.0
48.0	6.4	6.4	6.4	3.8	6.4	6.4	5.4	3.0
50.0	5.9	5.9	5.9	3.7	5.9	5.9	5.2	2.9
52.0	5.3	5.3	5.3	3.6	5.3	5.3	5.0	2.8
54.0	4.8	4.8	4.8	3.4	4.8	4.8	4.8	2.8
56.0	4.3	4.3	4.3	3.3	4.3	4.3	4.3	2.7
58.0	3.9	3.9	3.9	3.2	3.9	3.9	3.9	2.7
60.0	3.6	3.6	3.6	3.1	3.6	3.6	3.6	2.6
62.0	3.2	3.2	3.2	3.0	3.2	3.2	3.2	2.5

CRAWLER CRANE

起重性能参数表 Total rated lifting load

副起重臂额定起重量 Rated jib lifting capacity

幅度 Radius (m)	主臂 Boom 73m					
	副臂安装角10° Jib erection angle 10°			副臂安装角30° Jib erection angle 30°		
	副臂 Jib 12m	副臂 Jib 18m	副臂 Jib 24m	副臂 Jib 12m	副臂 Jib 18m	副臂 Jib 24m
18.0	15.0					
20.0	15.0					
22.0	15.0	12.0		13.0		
24.0	15.0	12.0	8.0	12.7		
26.0	15.0	12.0	8.0	12.4		
28.0	15.0	12.0	8.0	12.1	8.0	
30.0	14.0	12.0	8.0	11.8	8.0	
32.0	12.6	12.0	8.0	11.6	8.0	6.0
34.0	11.4	11.4	8.0	11.3	8.0	6.0
36.0	10.4	10.4	7.8	10.4	8.0	6.0
38.0	9.5	9.5	7.7	9.5	8.0	6.0
40.0	8.6	8.6	7.5	8.6	8.0	6.0
42.0	7.9	7.9	7.4	7.9	7.9	6.0
44.0	7.2	7.2	7.2	7.2	7.2	5.8
46.0	6.5	6.5	6.5	6.5	6.5	5.6
48.0	6.0	6.0	6.0	6.0	6.0	5.3
50.0	5.5	5.5	5.5	5.5	5.5	5.1
52.0	4.8	4.8	4.8	4.8	4.8	4.8
54.0	4.3	4.3	4.3	4.3	4.3	4.3
56.0	4.0	4.0	4.0	4.0	4.0	4.0
58.0	3.6	3.6	3.6	3.6	3.6	3.6
60.0	3.2	3.2	3.2	3.2	3.2	3.2
62.0	2.8	2.8	2.8	2.8	2.8	2.8

注:

- 1.表中所示起重量的单位为t。
- 2.表中所示起重量包括吊具及附件的重量。
- 3.副臂臂长为12m、18m时，倍率均为2，其余臂长倍率均为1。

Note:

- 1.The unit of lifting capacity is ton.
- 2.Lifting capacity in the table includes the weight of sling and accessories.
- 3.When jib length is 12m and 18m, parts of line is 2, when other jib lengths, parts of line is 1.